



Flexible elastic tape with high adhesion strength

COMPEGO is used to permanently seal overlaps, joints and connections for vapour-closed products. It is suitable for taping extruded polystyrene (XPS) foam insulation boards, polyethylene sheet (underslab damp-proofing membrane), foil-faced vapour-tight insulation boards, steel-skinned structurally insulated panels (SIPs).

- ✓ Highly elastic and flexible
- ✓ Waterproof adhesive
- ✓ Airtight connection for the life of the building
- ✓ Very low VOC rating in hazardous substance tests - tested according to ISO 16000



08 2024



Your local support

0800 PRO CLIMA (776 254)

Technical: support@proclima.co.nz | General: welcome@proclima.co.nz

www.proclima.co.nz





Flexible elastic tape with high adhesion strength

Technical Data

Backing	Elastic polyethylene film
Adhesive:	Acrylate contact adhesive
Release material:	Silicone-coated paper
Temperature resistance:	long term -40 °C to 90 °C
Installation temperature:	above -10 °C
Colour:	White / blue
Storage:	cool and dry

APPLICATION NOTES

Clean subsurface before applying tape. Adhesion is not possible on frozen surfaces. Materials to be sealed must not contain water-repellent substances (e.g., grease or silicone). Subsurface must also be sufficiently dry and stable. Permanent adhesion is achieved on all vapour barriers (e.g. those made of PE, PA, PP or aluminium).

Pre-treatment with TESCON® PRIMER RP is required for adhesion to porous substrates. Pre-treatment with TESCON® PRIMER RP is recommended in the case of substrates that have insufficient stability.

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal.

GENERAL CONDITIONS

Taped joints must not be subjected to tensile forces. Windproof, airtight, or rainproof taped joints can only be achieved on membranes installed without folds or creases.

Delivery Form

ID CODE	LENGTH	WIDTH	QTY
15357	25 m	60 mm	Box of 10 rolls
15385	25 m	100 mm	1 roll
15386	25 m	150 mm	1 roll



Your local support

0800 PRO CLIMA (776 254)

Technical: support@proclima.co.nz | General: welcome@proclima.co.nz

www.proclima.co.nz

