



TESCON EXTONSEAL® sill tape is a flexible flashing tape for use around framed joinery openings as part of flexible or rigid weather resistive barrier (WRB) systems. It provides optimum weather protection around penetration openings, under all conditions. TESCON EXTONSEAL® provides a wind tight and watertight adhesive seal to the substrate forming a weathertight sill to drain water safely to the outside.

- ✓ Excellent UV resistance (180 days exposure)
- ✓ Long-term durability
- ✓ Self-sealing around nail and screw penetrations
- ✓ Excellent adhesive strength
- ✓ Weathertight & airtight component of your WRB



24 03 2020



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





Technical Data

Carrier material:	elastic polyethylene (PE) film	
Core material:	butyl rubber modified with acrylate	
Release material:	silicone coted PE film	
UV stability and outdoor exposure:	180 Days	BRANZ Appraisal No. 815
Surface weight:	1.9 kg/m ²	EN 1849-2
Vapour classification:	Class 1	AS/NZS 4200.1 - 2017
Vapour resistance:	> 500 MN.s/g	ASTM E96
Installation temperature:	from -20 °C	
Temperature resistance:	long term -30 °C to +90 °C	
S _d value, equiv. air layer thickness:	> 100 m ± 0.02 m	ISO 12572 (equiv. 500 MNs/g)
Vapour permeance:	< 0.002 µg/N.s	

IMPORTANT INFORMATION

- Long term UV exposure before cladding up to 180 days (6 months).
- Self-sealing achieving water-tight nail and screw penetrations.
- Malleable and workable to easily form into corners and shapes.
- Super strong adhesion.

PRODUCT DESCRIPTION

TESCON EXTONSEAL® is a UV stabilised sill flashing tape for an essential part of your WRB system. Made from butyl rubber modified with acrylate it is malleable and easily workable into difficult to seal corners and junctions for optimal resistance to driving rain at window openings.

WEATHER EXPOSURE

This product is an essential component of a WRB system and designed to withstand up to 180 days direct exposure to UV and still fulfil the intended use for wind and water control for protection against driving rain. Exterior cladding should be detailed to prevent direct sunlight onto TESCON EXTONSEAL® in service.

APPLICATION NOTES

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long term durable seal.

Delivery Form

ID CODE	LENGTH	WIDTH	BACKING	QTY
14152	20 m	150 mm	90/60 split	1
14156	20 m	200 mm	140/60 split	1



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au

