



TruTool TKA 1500

Technical data



TruTool TKA 1500 without tool**TruTool TKA 1500 45° tool****MAXIMUM CHAMFER LENGTHS / MAXIMUM CHAMFER HEIGHTS**

Maximum chamfer length, steel 400 N/mm ²	15 mm	15 mm
Maximum chamfer height, steel 400 N/mm ²	10.6 mm	10.6 mm
Maximum chamfer length, steel 600 N/mm ²	12 mm	12 mm
Maximum chamfer height, steel 600 N/mm ²	8.5 mm	8.5 mm
Maximum chamfer length, steel 800 N/mm ²	10 mm	10 mm
Maximum chamfer height, steel 800 N/mm ²	7.1 mm	7.1 mm
Maximum chamfer length, aluminium 250 N/mm ²	15 mm	15 mm
Maximum chamfer height, aluminium 250 N/mm ²	10.6 mm	10.6 mm

RADII

Smallest inner radius	30 mm	30 mm
Smallest bore hole (Ø)	55 mm	55 mm

GENERAL

Minimum sheet thickness	3 mm + hs	3 mm + hs
Working speed (max.)	1.5 m/min	1.5 m/min
Nominal power consumption	2600 W	2600 W

DIMENSIONS

Length	679 mm	679 mm
Height	197 mm	197 mm

WEIGHT

Weight	10 kg	10 kg
--------	-------	-------